



**DIRECT-ATTACHED
SAS STORAGE**

T8



Featuring ATTO ExpressSAS

Host-Level Hardware RAID

RAID processing and recovery is self-contained and does not affect host computer CPU performance.

Sustained Performance

Configurable drive rebuild priority to maintain full performance while in recovery mode. Up to 50% faster drive rebuild than industry standard hardware RAID controllers.

Blazing-Fast Throughput

Upwards of 700MB per second reads and writes. The T8 supports multi-stream HD and 2K DI workflow.

One-Click Installation

Easy-to-use GUI with a multi-platform configuration utility and factory presets for plug-and-play operation.

Compatibility

Out-of-the-box support for Windows®, Linux, Mac®

**Designed for Post
Production and Content Creation**

ATTO

ATTO Technology, Inc.

ExpressSAS

3Gb/s
SAS/SATA RAID



Performance Specifications

RAID5

Normal Reads: 700MB/sec

Normal Writes: 500MB/sec

Drive Failure Reads: 700MB/sec

Drive Failure Writes: 500MB/sec

RAID6

Normal Reads: 600MB/sec

Normal Writes: 530MB/sec

Drive Failure Reads: 550MB/sec

Drive Failure Writes: 550MB/sec

Two Drive Failure Reads: 550MB/sec

Two Drive Failure Writes: 450MB/sec

Qualified Stream Count*

Avid Nitris DX / Final Cut Studio

✓ 3 Streams of 1080 29.97i 10bit

✓ 2 Streams of 1080 29.97i 4:4:4

Assimilate SCRATCH

✓ 1 Stream of 2K DPX 24fps

✓ 2 Streams of HD 10bit DPX

*Based on 60% full capacity; higher performance when the storage is empty.

Available Q4 2010

16TB Package:

T8 unit with one

ATTO ExpressSAS

R380 Controller for

Mac, Windows or Linux

For pricing, contact
Facilis Technology Sales
at sales@facilis.com or
phone +1 978-562-7022