



ExpressSAS Host Adapter Release v1.13 - Windows®

1. General Release Information

These product release notes define the new features, changes, known issues and release details that apply to the ExpressSAS Host Adapter products v1.13 that was released on 1/30/09. This information pertains to the Microsoft® Windows OS including Windows XP, Vista, Server 2003, and Server 2008 for x86 and x64 platforms.

2. Changes

- **Version 1.13 (Released 1/30/2009)**
 - **Note:** It is recommended that firmware dated 01/26/09 be utilized with this driver release.
 - The following apply to changes made from v1.12 to v1.13
 - **Incident Resolutions/Bug Fixes/Changes**
 - Resolved an issue regarding the HBA not coming up at full speed under PCI Express 2.0. The problem occurred when using a specific Intel chipset, the MCH 5400

- **Version 1.12 (Released 11/18/2008)**
 - **Note:** It is recommended that firmware dated 2008_11_18 be utilized with this driver release.
 - The following apply to changes made from v1.10 to v1.12
 - **New Features**
 - Implemented support to disable SATA NCQ
 - Implemented support to disable target ID assignment based on SAS address
 - Implemented support for the H3RO
 - Improve discovery processing to ensure discovery is retried when the firmware returns a partial topology

 - **Incident Resolutions/Bug Fixes/Changes**
 - In firmware version 2.01 and later, verified the length of writes to correct an issue with ATAPI devices
 - Implemented support to disable target ID assignment based on SAS address
 - Resolved an issue where event log entries during the initial driver load and adapter initialization would always have an adapter number of one

- **Version 1.10 (Released 5/14/2008)**
 - **Note:** It is recommended that firmware dated 2008_05_09 be utilized with this driver release.
 - The following apply to changes made from v1.00 to v1.10
 - **New Features**
 - **Added support for ExpressSAS H30F:** With this release, ATTO has released an ExpressSAS H30F Host Adapter model with 16 internal mini-SAS ports for increased connectivity.
 - **Added full support for Server 2008**

 - **Incident Resolutions/Bug Fixes/Changes**
 - Support added for ExpressSAS H30F

- Initialization enhancements incorporated to support transport firmware updates
 - Improved power management functionality
 - Improved handling of event log to prevent logging from being stopped if the buffer became full
 - Enhanced support for applications to perform SMP commands
 - After initial discovery has completed, devices are now presented to the OS in order of ascending SAS address with SMP devices sorted last
 - Improved SATA device affiliation behind expanders when devices are moved between two adapters
- **Version 1.00 (Released 10/19/2007)**
 - Initial release for the ExpressSAS H380 and H308 Host adapters

3. Known Issues/Advisements

- In some instances, tape I/O can fail during simultaneous SATA disk I/O and SAS tape I/O.
- When booting off a drive attached to the ExpressSAS host adapter, the system will not automatically power off after entering a state of hibernation. A user can manually power off the system and later resume from hibernation without issue.
- Reference DOS/BIOS and Configuration Tool release notes for additional information

4. Affected Products

Product Name	SKU
ExpressSAS H308 Host Adapter	ESAS-H308-000
ExpressSAS H380 Host Adapter	ESAS-R380-000
ExpressSAS H30F Host Adapter	ESAS-H30F-000

5. Contacting ATTO Support

ATTO Technology, Inc. is renowned for its technical support services. ATTO's goal is to provide you the quickest response possible for your technical support needs, and is available Monday-Friday, 8:00 AM to 8:00 PM EST (except holidays and plant closings).

ATTO Technical Support can be contacted via phone or email:

- Phone: 716.691.1999 ext. 242
- E-Mail: techsupport@attotech.com