



ExpressSAS Host Adapter 6 Gb v1.20 – Mac

1. General Release Information

These product release notes define the new features, changes, known issues and release details that apply to the ExpressSAS Host adapter products v1.20 that was released on 07/31/2009. This information pertains to Mac.

2. Changes

- **Version 1.20 (Released 07/31/2009)**
 - **Note:** It is recommended that firmware dated 07/29/09 be utilized with this driver release.
 - The following applies to release v1.20
 - **New Features, Enhancements and Changes**
 - Documented support for Snow Leopard.
 - Enhanced firmware which contributed in an up to 25% increase in throughput.
 - Added the Read/Write Time Out Duration properties to specify timeouts for read/write commands. The timeout value is 30 seconds. This timeout applies only to devices for which Mac OS X provides an in-box driver (SCSI device types 0, 5, 7, and 14).
 - The supported expander chain depth was increased from 8 to 10.
 - Transport layer retries are explicitly enabled on all commands for SAS 2.0 compliant devices instead of being enabled in the device's mode pages.
 - All command retries are disabled for sequential (e.g. tape) devices.
 - SMP PHY Control command for clearing SATA affiliations improved. Uses the hard reset function instead of the clear affiliation function.
 - Expander enhancements which include discovery process reorganization for clearing SATA affiliations. All devices reported to the OS will have sequential target IDs starting with zero.
 - The heartbeat mechanism has been redesigned to improve I/O resources allocation.
 - Confirmation of I/O completion to the OS prior to reporting a device removal.
 - SCSI check status for data phase errors and other bus events that occur due to signal integrity problems are now retried
 - When a port is reset due to a task management command timeout, the aborted collateral is retried.
 - Enhanced event logging to include retried commands and added timestamps.
 - Added support to the SMP API for discovering direct attached devices. Changed the scatter/gather allocation to improve performance and conserve memory.
 - Improved optimizations and memory allocation to expander discovery process to increase number of drives that can be discovered.
 - The OPEN REJECT RETRY interval is set to 5 μ s

- **Version 1.10 (Released 03/24/2009)**
 - **Note:** It is recommended that firmware dated 03/20/09 be utilized with this driver release.
 - The following applies to release v1.10
 - **New Features, Enhancements and Changes**
 - Added the Device Name field to the SAS Identify Address Frame (an optional field added in SAS 2.0).
 - Resolved an issue during initial device discovery that could result in a driver crash if the device rejects a discovery command.
 - Resolved issues with discovery processing when a discovery command timed out
 - SATA devices behind expanders are no longer reset during discovery
 - Improved SATA NCQ processing so performance is maintained as the queue depth increases
 - Improved port down cleanup to ensure all I/O is completed before destroying devices when multiple ports are instantiated
 - Resolved an issue with SCSI-to-ATA translation of the WRITE AND VERIFY commands that would allow NCQ commands to be started between the write and verify phases
 - Now support SMP API
 - Added timeout processing for commands issued through the SMP API
 - SATA NCQ is disabled in NVRAM by default

- **Version 1.01 (Released 02/18/2009)**
 - **Note:** It is recommended that firmware dated 01/28/09 be utilized with this driver release.
 - The following applies to release v1.01
 - **New Features, Enhancements and Changes**
 - Resolved issues that may cause the driver to crash or hang if a device rejects a discovery command on initial load.
 - Resolved any unexpected target ID changes after a cable pull and reinsertion, when a SATA device is connected behind an expander.

- **Version 1.00 (Released 12/11/2008)**
 - **Note:** It is recommended that firmware dated 12/05/08 be utilized with this driver release.
 - The following applies to release v1.00
 - **New Features, Enhancements and Changes**
 - Initial release of ExpressSAS H608 and H680

3. Known Issues/Advisements

- Please refer to the DOS release notes for any known firmware issues.
- SAT exceptions: (SCSI-to-ATA Translation for SATA support). The following SCSI commands are not translated: FORMAT UNIT, REASSIGN BLOCKS, SECURITY PROTOCOL IN, and SECURITY PROTOCOL OUT.
- Sleep, or system standby, is supported on PowerPC Macs, however the sleep light will not pulsate and the fan will increase to maximum speed until the system is awakened. "Deep" sleep is fully supported on Intel Macs.

4. Affected Products

Product Name	SKU
ExpressSAS H680 Host Adapter	ESAS-H680-000
ExpressSAS H608 Host Adapter	ESAS-H608-000
ExpressSAS H6F0 Host Adapter	ESAS-H6F0-000
ExpressSAS H60F Host Adapter	ESAS-H60F-000
ExpressSAS H644 Host Adapter	ESAS-H644-000

5. Contacting ATTO Support

ATTO Technology, Inc. is renowned for its technical support services. ATTO's goal is to provide you the quickest response possible for your technical support needs, and is available Monday-Friday, 8:00 AM to 8:00 PM EST (except holidays and plant closings).

ATTO Technical Support can be contacted via phone or email:

- Phone: 716.691.1999 ext. 242
- E-Mail: techsupport@attotech.com