



## ExpressSAS 6Gb RAID Release v2.25 – Windows®

### 1. General Release Information

---

These product release notes define the new features, changes, known issues and release details that apply to the ExpressSAS 6Gb RAID adapter product v2.25 that was released on March 12, 2013. This information pertains to the Microsoft Windows OS including Windows 2000 (x86 only), XP (x86 and x64), Vista (x86 and x64), Windows 7 (x86 and x64), Windows 8 (x86 and x64), Server 2003 (x86 and x64), Server 2008 (x86 and x64) and Server 2012 (x86 and x64) platforms.

### 2. Changes

---

- **Version 2.25 (Released 3/12/2013)**
  - **Note:** It is recommended that firmware dated 3/4/2013 be used with this driver release.
  - **New Features, Enhancements and Changes**
    - Pass through devices are persistently mapped to prevent data corruption.
    - We now notify the firmware when the driver is shutting down.
    - Added support for the atsasphy and atsastop CLI tools.
    - Added support for additional firmware based functionality in the atinfo and attrace CLI tools.
    - Added support for the SMP API.
    - Added support for CSMI.
    - Redesigned power management to prevent Windows 8 from crashing when resuming from sleep.
    - Return a zero size file if the firmware core dump is not present.
    - Added support for reading the SAS address of front-end devices.
    - Fixed an issue where the entire RAID group name may not be displayed in event logs.
- **Version 2.19 (Released 9/27/2012)**
  - **Note:** It is recommended that firmware dated 9/27/2012 be used with this driver release.
  - **New Features, Enhancements and Changes**
    - This driver version supports ROC version B2 hardware.
    - A notification is now sent when coming out of power management that the firmware has been reset.
    - Storport performance optimizations are disabled.
- **Version 2.18 (Released 8/27/2012)**
  - **Note:** It is recommended that firmware dated 8/24/2012 be used with this driver release.
  - **New Features, Enhancements and Changes**
    - Lowered the amount of memory allocated in dump mode.
    - Fixed a rare case where adapter could go degraded after returning from sleep.
    - Added support for extracting a firmware core dump using the ATTO CLI Tool 'attrace'

- **Version 2.17 (Released 2/22/2012)**
  - **Note:** It is recommended that firmware dated 2/17/2012 be used with this driver release.
  - **New Features, Enhancements and Changes**
    - Added support for the atreset CLI tool.
    - Corrected an issue where resources are exhausted while command coalescing.
  
- **Version 2.15 (Released 12/15/2011)**
  - **Note:** It is recommended that firmware dated 12/15/2011 be used with this driver release.
  - **New Features, Enhancements and Changes**
    - Several enhancements have been made to chip reset processing.
    - Enhancements have been made to error recovery and task management while using command coalescing.
    - Added MSI support.
    - Report which type of boot image is present on the card with Configuration Tool version 4.02 and later (BIOS, EFI 32-bit or EFI 64-bit).
  
- **Version 2.11 (Released 10/14/2011)**
  - **Note:** It is recommended that firmware dated 10/12/2011 be used with this driver release.
  - **New Features, Enhancements and Changes**
    - Several enhancements have been made throughout the driver to report errors and operate correctly in degraded mode. Enhancements have been made in the APIs for NVRAM, flashing and RAID management.
    - Resolved an issue with command coalescing.
  
- **Version 2.10 (Released 06/29/2011)**
  - **Note:** It is recommended that firmware dated 06/22/2011 be used with this driver release.
  - **New Features, Enhancements and Changes**
    - The driver to firmware communication mechanism has been changed. Driver v2.10, or later, is required to support firmware v2.50, and later. Additionally, the v2.10 driver supports earlier firmware versions from v2.00 up through v2.20.
    - The maximum transfer size value has been lowered to 4MB.
  
- **Version 2.07 (Released 04/21/2011)**
  - **Note:** It is recommended that firmware dated 04/18/2011 be used with this driver release.
  - **New Features, Enhancements and Changes**
    - Added support to the R60F, R608 and R644 for virtual SES
  
- **Version 2.06 (Released 03/25/2011)**
  - **Note:** It is recommended that firmware dated 03/25/2011 be utilized with this driver release.
  - **New Features, Enhancements and Changes**
    - Increased performance for transactional and streaming applications.
    - Improved handling and discovery of drives during system reboot and when drives are pulled or reset.
    - Expanded reporting for disk drive Vendor ID.
    - NCQ is now enabled by default.
    - Resolved various, minor incident fixes to improve overall performance
  
- **Version 2.05 (Released 02/11/2011)**
  - **Note:** It is recommended that firmware dated 02/11/2011 be utilized with this driver release.
  - **New Features, Enhancements and Changes**
    - Performance improvements in IOPs and MB/s applications.
    - CacheAssure performance improvements when in High Protection mode.
    - SAS Multiplexing implemented. This enables the user to achieve performance improvements with 6Gb RAID when using slower 3Gb drives.
    - Improved compatibility between the operating systems range of physical memory and the physical memory of the hardware.
    - Increased the default scatter/gather list size to 512 bytes.

- **Version 2.00 (Released 9/22/2010)**
  - **Note:** It is recommended that firmware dated 09/17/2010 be utilized with this driver release.
  - **Note:** "Any upgrade from a previous version to 2.00 for the driver and firmware must be done in a specific order. Version 2.00 firmware must be updated first with a flashbundle using the ATTO Configuration Tool. Once the new firmware is flashed, "DO NOT REBOOT," the 2.00 driver should be loaded. Your system will appear to freeze for up to three minutes while the new driver is loaded. A reboot is required to use the new update."
  - **New Features, Enhancements and Changes**
    - Initial Release and added support for the R60F.
    - The driver to firmware communication mechanism has been improved. Driver versions 2.00 and later are only supported with version 2.00 and later firmware.
- **Version 1.00 (Released 5/21/2010)**
  - **Note:** It is recommended that firmware dated 05/20/10 be utilized with this driver release.
  - **New Features, Enhancements and Changes**
    - Initial release for the R644, R680 and R608.

### Known Issues/Advisements

---

- See known firmware issues in the DOS release notes.

### 3. Affected Products

---

Product Name	SKU
ExpressSAS R644 RAID Adapter	ESAS-R644-000
ExpressSAS R680 RAID Adapter	ESAS-R680-000
ExpressSAS R608 RAID Adapter	ESAS-R608-000
ExpressSAS R60F RAID Adapter	ESAS-R60F-000
ExpressSAS R644 RAID Adapter with CacheAssure	ESAS-R644-C00
ExpressSAS R680 RAID Adapter with CacheAssure	ESAS-R680-C00
ExpressSAS R608 RAID Adapter with CacheAssure	ESAS-R608-C00
ExpressSAS R60F RAID Adapter with CacheAssure	ESAS-R60F-C00

### 4. Contacting ATTO Support

---

ATTO Technology, Inc. is renowned for its technical support services. ATTO's goal is to provide you the quickest response possible for your technical support needs, and is available Monday-Friday, 8:00 AM to 6:00 PM EST (except holidays and plant closings).

ATTO Technical Support can be contacted via phone or email:

- Phone: 716.691.1999 ext. 242
- E-Mail: [techsupport@attotech.com](mailto:techsupport@attotech.com)