



ATTO Technology, Inc.

ExpressSAS H380 Low-Profile SAS Host Adapter

Product Features

Blazing Fast Performance

- Up to 3-Gb/sec per port transfer rates with SAS, SATA and SATA II attachment
- Increased bandwidth through x8 PCI Express host interface
- Point-to-point technology delivers full throughput to each connected storage device

Smooth Data Streaming

- Alleviate data transfer bottlenecks and move data more efficiently while managing latency with ATTO's exclusive ADS™ technology
- Improve I/O through optimized data movement

One Click Installation

- One-click installation allows for quick and easy set-up
- Simple host based utility for effortless configuration
- BIOS setup utility provides flexibility for custom applications

3-Gb SAS/SATA II Connectivity

ATTO introduces the ExpressSAS H380 Low-Profile Host Adapter. Providing 3-Gb SAS/SATA II connectivity and eight external ports, the ATTO SAS Host Adapter is ideal for both IT and digital video environments that require a high level of performance.

The ATTO ExpressSAS host adapter product family provides enhanced reliability and performance thanks to more than 15 years of experience with SCSI hardware and storage connectivity solutions. Using the latest in PCI Express bus technology and an eight external port configuration, the ATTO ExpressSAS H380 Host Adapter delivers blazing fast performance with transfer rates of up to 3-Gb per second per port.

The ATTO ExpressSAS Host Adapters are engineered for the most stringent IT server and digital media workgroup environments and are compatible with multiple operating systems, applications, and drives.

The easy-to-use utility enables management, monitoring, and configuration. ATTO also incorporates its field proven Advanced Data Streaming (ADS™) technology to meet the most demanding performance requirements of data intensive applications. In addition, ATTO provides industry standard PCIe to SAS control using Serial SCSI Protocol (SSP), Serial ATA Tunneling Protocol (STP), and Serial Management Protocol (SMP).

Technical Highlights

- x8 PCIe host interface
- True low-profile form factor
- 8 external ports
- Outstanding performance with up to 3-Gb/sec per port
- SAS, SATA and SATA II connectivity
- Supports up to 256 SAS/SATA drives
- Exclusive Advanced Data Streaming (ADS™) technology
- User friendly configuration utility
- Driver support for Windows®, Linux and Mac® OS X
- RoHS Compliant
- 2-year standard product warranty

Technical Specification
ExpressSAS H380 Host Adapter

Host Adapter

For More Information:
www.ATTOTech.com
or to Purchase:
www.ATTOSTore.com
(716) 691-1999



ExpressSAS Low-Profile Host Adapter

ATTO Technology, Inc.

3-Gb SAS/SATA II Connectivity

Hardware Specifications	
Applications	<ul style="list-style-type: none"> • Support for IT server and digital media workgroup solutions requiring high-bandwidth and reliability. Applications include audio/video, VOD, fixed content, database and other data intensive environments.
Maximum Transfer Rate	<ul style="list-style-type: none"> • Up to 3-Gb/sec per port
Advanced Capabilities	<ul style="list-style-type: none"> • Device support for SAS, SATA and SATA II • User friendly GUI for quick and easy configuration • Advanced management functions • External LEDs for on-line status • PC Bios bootability
PCI Bus Specifications	<ul style="list-style-type: none"> • x8 PCI Express host interface • Supports PCI Express Base Spec 1.0a
Connectors	<ul style="list-style-type: none"> • Two x4 External Mini SAS connectors
Software Specifications	
Driver Support	<ul style="list-style-type: none"> • Windows® Server 2003, XP, 2000 • Mac® OS X (10.4.x) • Linux (Red Hat and SuSE)
Agency Approvals	
Safety and Environmental	<ul style="list-style-type: none"> • FCC Rules, Part 15, Class B • CE Mark: CISPR 22:2002/EN55022:2002, Class B
Compliance	<ul style="list-style-type: none"> • RoHS Compliant
Environmental & Physical Specifications	
Dimensions	<ul style="list-style-type: none"> • Conforms to PCI low-profile form factor specifications • Length 6.600" • Height 2.713"
Operating Environment	<ul style="list-style-type: none"> • Temperature: 0-40° C (32°-104°F) • Humidity: 5 - 95% non-condensing
Storage Environment	<ul style="list-style-type: none"> • Temperature: -40°-70°C (-40°-157°F) • Humidity: 5 - 95% non-condensing
Power	<ul style="list-style-type: none"> • Conforms to PCIe spec 1.0a
Airflow	<ul style="list-style-type: none"> • 150 lf/m (min) recommended
Ordering Information	
Model Number	<ul style="list-style-type: none"> • ESAS-H380-000 (Includes standard height and low-profile bracket)

