



ATTO Technology, Inc.

ExpressSAS R30F 16 Port SAS RAID Adapter

3-Gb SAS/SATA II Connectivity with Integrated RAID Support



Product Features

Blazing Fast Performance

- Up to 3-Gb/sec per port transfer rates with SAS, SATA and SATA II attachment
- Increased bandwidth through x8 PCI Express host interface
- Point-to-point technology delivers full throughput to each connected storage device

Smooth Data Streaming

- Alleviate data transfer bottlenecks and move data more efficiently while managing latency with ATTO's exclusive ADS™ technology
- Improve I/O through optimized data movement

One Click Installation

- One-click installation allows for quick and easy set-up
- Simple GUI based utility for effortless adapter configuration
- BIOS setup utility provides flexibility for custom applications

Increased Productivity

- Run longer, faster and smoother with DriveAssure™
- Uninterrupted data flow provides consistent frame transfers
- Improved drive lifespan

The ATTO ExpressSAS R30F RAID Adapter combines 3-Gb SAS/SATA II connectivity with sixteen internal ports and integrated RAID support making it the ideal SAS RAID adapter for both IT and digital media environments requiring flexible connectivity options and the highest performance with data protection.

The ATTO ExpressSAS host adapter product family provides enhanced reliability and performance thanks to more than 15 years of experience with SCSI hardware and storage connectivity solutions. Using PCI Express bus technology and sixteen internal port configuration, the ATTO ExpressSAS R30F RAID adapter delivers blazing fast performance with transfer rates of up to 3-Gb per second per port. With four internal x4 Mini SAS connectors, the R30F provides connectivity of up to 16 internal SAS/SATA targets. The R30F also features 512MB of ECC-protected DDR2 DRAM to allow support for multiple RAID groups.

The ATTO ExpressSAS R30F RAID adapter is engineered for the most stringent IT server and digital media workgroup environments. To satisfy the data protection requirements of these environments, ATTO leverages it's time tested ATTO RAID Stack (ARS™) technology based on a proven RAID core that is compatible with multiple operating systems, applications, and drives.

The easy-to-use GUI utility enables RAID management, monitoring, and configuration. ATTO also incorporates it's field proven Advanced Data Streaming (ADS™) technology to meet the most demanding performance requirements of data intensive applications. In addition, ATTO provides industry standard PCIe to SAS control using Serial SCSI Protocol (SSP), Serial ATA Tunneling Protocol (STP), and Serial Management Protocol (SMP)

Technical Highlights

- x8 PCIe host interface
- Half-height
- 16 internal ports
- Outstanding performance with up to 3-Gb/sec per port
- Highly configurable RAID (0, 1, 4, 5, 6, 10, 50, 60, JBOD and DVRAID support)
- SAS, SATA and SATA II connectivity
- Internally connect up to 16 direct attached drives
- Exclusive Advanced Data Streaming (ADS™) technology
- DriveAssure™
- SNMP support
- User friendly GUI configuration utility
- Driver support for Windows®, Linux® and Mac® OS X
- RoHS Compliant
- 3-year standard

Technical Specification
ExpressSAS R30F RAID Adapter

RAID Adapter

For More Information:
www.ATTOTech.com
or to Purchase:
www.ATTOSTore.com
(716) 691-1999



ExpressSAS 16 Port RAID Adapter

ATTO Technology, Inc.

3-Gb SAS/SATA II Connectivity with Integrated RAID Support

Hardware Specifications	
Applications	<ul style="list-style-type: none"> Support for IT server and digital media workgroup solutions requiring high-bandwidth and data protection. Applications include audio/video, VOD, fixed content, database and other data intensive environments.
Maximum Transfer Rate	<ul style="list-style-type: none"> Up to 3-Gb/sec per port
Advanced Capabilities	<ul style="list-style-type: none"> Device support for SAS, SATA and SATA II SES Support S.M.A.R.T Support SNMP Support for Staggered drive spin-up Pass-through mode to support tape devices Support for RAID levels 0, 1, 4, 5,6, 10, 40, 50, 60, JBOD and DVRAID On-line capacity expansion (OCE) Hot spare, auto-rebuild Native Command Queuing Cache memory—512MB ECC protected memory User friendly GUI for RAID setup
PCI Bus Specifications	<ul style="list-style-type: none"> x8 PCI Express host interface Supports PCI Express Base Spec 1.0a
Connectivity	<ul style="list-style-type: none"> Easy-to-install low-profile connection bracket; full-height bracket included in Finished Goods packaging Four x4 Internal Mini SAS (SFF-8087) connectors
Software Specifications	
Driver Support	<ul style="list-style-type: none"> Windows® Server 2003, 2008, XP, Vista, 7 Mac® OS X (10.4.x - 10.6.x) Linux® (Red Hat and SuSE)
Agency Approvals	
Safety and Environmental	<ul style="list-style-type: none"> FCC Rules, Part 15, Class B CE Mark: CISPR 22:2002 EN55022:2002, Class B
Compliance	<ul style="list-style-type: none"> RoHS Compliant
Environmental & Physical Specifications	
Dimensions	<ul style="list-style-type: none"> Length 8.640" Height 2.900"
Operating Environment	<ul style="list-style-type: none"> Temperature: 0-60° C (32°-140°F) Humidity: 5 - 95% non-condensing
Storage Environment	<ul style="list-style-type: none"> Temperature: -40°-70°C (-40°-157°F) Humidity: 5 - 95% non-condensing
Power	<ul style="list-style-type: none"> 12V @ 1.44A 3.3V @ 0.54A (W - typical): 17W
Airflow	<ul style="list-style-type: none"> 150 lf/m (min) recommended
Ordering Information	
Model Number	<ul style="list-style-type: none"> ESAS-R30F-000 (RoHS)

